

Technical parameters							
Model(s):		ACHP-H16/4R3HA-ME		ACHP-H16/4R3HA-M(NE)		ACHP-H16/5R3HA-M	
Air-to-water heat ump:		yes					
Water-to-water heat pump:		no					
Brine-to-water heat pump:		no					
Low-temperature heat pump:		no					
Equipped with a supplementary heater:		no					
Heat pump combination heater:		no					
Declared climate condition		Warmer					
Declared temperature application		Low					
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output(*)	Prated	13.1	kW	Seasonal space heating energy efficiency	ηs	246	%
Declared capacity for heating for part load at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	-	kW	Tj = -7°C	COPd	-	-
Tj = +2°C	Pdh	12.97	kW	Tj = +2°C	COPd	3.35	-
Tj = +7°C	Pdh	8.41	kW	Tj = +7°C	COPd	5.31	-
Tj = +12°C	Pdh	3.87	kW	Tj = +12°C	COPd	8.11	-
Tj = bivalent temperature	Pdh	8.41	kW	Tj = bivalent temperature	COPd	5.31	-
Tj = operation limit temperature	Pdh	12.97	kW	Tj = operation limit temperature	COPd	3.35	-
For air-to-water heat pumps: Tj = -15°C (ifTOL<-20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C(ifTOL<-20°C)	COPd	-	-
Bivalent temperature	Tbiv	7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval capacity for heating	Ppsych	-	kW	Cycling interval efficiency	COPcyc	-	-
Degradation co-efficient(**)	Cdh	0.9	-	Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplemantary heater			
Off mode	P ^{OFF}	0.020	kW	Rated heat output (*)	Psup	0.13	kW
Thermostat-off mode	P ^{TO}	0.030	kW	Type of energy input	Electricity		
Standby mode	P ^{SB}	0.020	kW				
Crankcase heater mode	P ^{CK}	0.000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	4650	m³/h
Sound power levelL	LWA	-	dB	For water-/brine-to-water heat pumps:Rated brine or water flow rate, outdoor heat exchanger	-	-	m³/h
Annual energy consumption	QHE	2812	kWh				
For heat pump combination heater							
Declaed load profile	-			Water heating energy efficiency	Hwh	-	%
Daily electricity consumption	Qelec	-	kWh	Daily fuel consumption	Qfuel	-	kWh
Contact details	AUX Co., Ltd 1166 Mingguang North Road, Jiangshan Yinzhou District, Ningbo, 315191 Zhejiang, China						
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9							

Technical parameters							
Model(s):		ACHP-H16/4R3HA-ME		ACHP-H16/4R3HA-M (NE)		ACHP-H16/5R3HA-M	
Air-to-water heat ump:		yes					
Water-to-water heat pump:		no					
Brine-to-water heat pump:		no					
Low-temperature heat pump:		no					
Equipped with a supplementary heater:		no					
Heat pump combination heater:		no					
Declared climate condition		Warmer					
Declared temperature application		Medium					
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output(*)	Prated	14.1	kW	Seasonal space heating energy efficiency	ηs	175	%
Declared capacity for heating for part load at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	-	kW	Tj = -7°C	COPd	-	-
Tj = +2°C	Pdh	13.97	kW	Tj = +2°C	COPd	2.48	-
Tj = +7°C	Pdh	9.06	kW	Tj = +7°C	COPd	3.58	-
Tj = +12°C	Pdh	4.03	kW	Tj = +12°C	COPd	6.05	-
Tj = bivalent temperature	Pdh	9.06	kW	Tj = bivalent temperature	COPd	3.58	-
Tj = operation limit temperature	Pdh	13.97	kW	Tj = operation limit temperature	COPd	2.48	-
For air-to-water heat pumps: Tj = -15°C (ifTOL<-20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C (ifTOL<-20°C)	COPd	-	-
Bivalent temperature	Tbiv	7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval capacity for heating	Pcyc	-	kW	Cycling interval efficiency	COPcyc	-	-
Degradation co-efficient(**)	Cdh	0.9	-	Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	POFF	0.020	kW	Rated heat output (*)	Psup	0.13	kW
Thermostat-off mode	PTO	0.030	kW	Type of energy input	Electricity		
Standby mode	p _{SB}	0.020	kW				
Crankcase heater mode	PCK	0.000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	4650	m³/h
Sound power levelL	LWA	-	dB	For water-/brine-to-water heat pumps:Rated brine or water flow rate, outdoor heat exchanger	-	-	m³/h
Annual energy consumption	QHE	4233	kWh				
For heat pump combination heater							
Declaed load profile	-			Water heating energy efficiency	Hwh	-	%
Daily electricity consumption	Qelec	-	kWh	Daily fuel consumption	Qfbel	-	kWh
Contact details	AUX Co., Ltd 1166 Mingguang North Road, Jiangshan Yinzhou District, Ningbo, 315191 Zhejiang, China						
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh =0.9							

Technical parameters							
Model (s):		ACHP-H16/4R3HA-ME		ACHP-H16/4R3HA-M(NE)		ACHP-H16/5R3HA-M	
Air-to-water heat ump:		yes					
Water-to-water heat pump:		no					
Brine-to-water heat pump:		no					
Low-temperature heat pump:		no					
Equipped with a supplementary heater:		no					
Heat pump combination heater:		no					
Declared climate condition		Average					
Declared temperature application		Low					
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output(*)	Prated	16.1	kW	Seasonal space heating energy efficiency	ηs	193	%
Declared capacity for heating for part load at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	14.24	kW	Tj = -7°C	COPd	3.04	-
Tj = +2°C	Pdh	8.67	kW	Tj = +2°C	COPd	4.70	-
Tj = +7°C	Pdh	5.57	kW	Tj = +7°C	COPd	6.62	-
Tj = +12°C	Pdh	2.48	kW	Tj = +12°C	COPd	8.91	-
Tj = bivalent temperature	Pdh	14.24	kW	Tj = bivalent temperature	COPd	3.04	-
Tj = operation limit temperature	Pdh	12.31	kW	Tj = operation limit temperature	COPd	2.67	-
For air-to-water heat pumps: Tj = -15°C(ifTOL<-20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C(ifTOL<-20°C)	COPd	-	-
Bivalent temperature	Tbiv	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Pcyc	-	kW	Cycling interval efficiency	COPcyc	-	-
Degradation co-efficient(**)	Cdh	0.9	-	Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	POFF	0.020	kW	Rated heat output (*)	Psup	3.79	kW
Thermostat-off mode	PTO	0.030	kW	Type of energy input	Electricity		
Standby mode	PSB	0.020	kW				
Crankcase heater mode	PCK	0.000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	4650	m³/h
Sound power leveL	LWA	-	dB	For water-/brine-to-water heat pumps:Rated brine or water flow rate, outdoor heat exchanger	-	-	m³/h
Annual energy consumption	QHE	6786	kWh				
For heat pump combination heater							
Declaed load profile	-			Water heating energy efficiency	Hwh	-	%
Daily electricity consumption	Qelec	-	kWh	Daily fuel consumption	Qfuel	-	kWh
Contact details	AUX Co., Ltd 1166 Mingguang North Road, Jiangshan Yinzhou District, Ningbo, 315191 Zhejiang, China						
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9							

Technical parameters							
Model(s):		ACHP-H16/4R3HA-ME ACHP-H16/4R3HA-M(NE) ACHP-H16/5R3HA-M					
Air-to-water heat ump:		yes					
Water-to-water heat pump:		no					
Brine-to-water heat pump:		no					
Low-temperature heat pump:		no					
Equipped with a supplementary heater:		no					
Heat pump combination heater:		no					
Declared climate condition		Average					
Declared temperature application		Medium					
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output(*)	Prated	14	kW	Seasonal space heating energy efficiency	ηs	137	%
Declared capacity for heating for part load at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	12.38	kW	Tj = -7°C	COPd	2.06	-
Tj = +2°C	Pdh	7.54	kW	Tj = +2°C	COPd	3.50	-
Tj = +7°C	Pdh	4.85	kW	Tj = +7°C	COPd	4.33	-
Tj = +12°C	Pdh	2.15	kW	Tj = +12°C	COPd	6.97	-
Tj = bivalent temperature	Pdh	12.38	kW	Tj = bivalent temperature	COPd	2.06	-
Tj = operation limit temperature	Pdh	10.50	kW	Tj = operation limit temperature	COPd	1.80	-
For air-to-water heat pumps: Tj = -15°C (ifTOL<-20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C (ifTOL<-20°C)	COPd	-	-
Bivalent temperature	Tbiv	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Pcyc	-	kW	Cycling interval efficiency	COPcyc	-	-
Degradation co-efficient(**)	Cdh	0.9	-	Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplemantary heater			
Off mode	P OFF	0.020	kW	Rated heat output (*)	Psup	3.5	kW
Thermostat-off mode	P TO	0.030	kW	Type of energy input	Electricity		
Standby mode	P SB	0.020	kW				
Crankcase heater mode	P CK	0.000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	4650	m³/h
Sound power level.	LWA	68	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m³/h
Annual energy consumption	QHE	8253	kWh				
For heat pump combination heater							
Declaед load profile	-			Water heating energy efficiency	Owh	-	%
Daily electricity consumption	Qelec	-	kWh	Daily fuel consumption	Qfuel	-	kWh
Contact details	AUX Co., Ltd 1166 Mingguang North Road, Jiangshan Yinzhou District, Ningbo, 315191 Zhejiang, China						
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9							

Technical parameters							
Model(s):		ACHP-H16/4R3HA-ME ACHP-H16/4R3HA-M(NE) ACHP-H16/5R3HA-M					
Air-to-water heat ump:		yes					
Water-to-water heat pump:		no					
Brine-to-water heat pump:		no					
Low-temperature heat pump:		no					
Equipped with a supplementary heater:		no					
Heat pump combination heater:		no					
Declared climate condition		Colder					
Declared temperature application		Low					
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output(*)	Prated	13.7	kW	Seasonal space heating energy efficiency	ηs	157	%
Declared capacity for heating for part load at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	8.31	kW	Tj = -7°C	COPd	3.37	-
Tj = +2°C	Pdh	5.26	kW	Tj = +2°C	COPd	4.86	-
Tj = +7°C	Pdh	3.62	kW	Tj = +7°C	COPd	6.49	-
Tj = +12°C	Pdh	3.34	kW	Tj = +12°C	COPd	7.40	-
Tj = bivalent temperature	Pdh	11.22	kW	Tj = bivalent temperature	COPd	2.43	-
Tj = operation limit temperature	Pdh	8.88	kW	Tj = operation limit temperature	COPd	1.97	-
For air-to-water heat pumps: Tj = -15°C (ifTOL<-20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C (ifTOL<-20°C)	COPd	-	-
Bivalent temperature	Tbiv	-15	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-22	°C
Cycling interval capacity for heating	Pcyc	-	kW	Cycling interval efficiency	COPcyc	-	-
Degradation co-efficient(**)	Cdh	0.9	-	Heating water operating limit temperature	WTOL	52	°C
Power consumption in modes other than active mode				Supplemantary heater			
Off mode	P OFF	0.020	kW	Rated heat output (*)	Psup	4.82	kW
Thermostat-off mode	°PTO	0.030	kW	Type of energy input	Electricity		
Standby mode	P SB	0.020	kW				
Crankcase heater mode	°PCK	0.000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	4650	m³/h
Sound power level.	LWA	-	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m³/h
Annual energy consumption	QHE	8438	kWh				
For heat pump combination heater							
Declaед load profile	-			Water heating energy efficiency	Owh	-	%
Daily electricity consumption	Qelec	-	kWh	Daily fuel consumption	Qfuel	-	kWh
Contact details	AUX Co., Ltd 1166 Mingguang North Road, Jiangshan Yinzhou District, Ningbo, 315191 Zhejiang, China						
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9							

Technical parameters							
Model(s):		ACHP-H16/4R3HA-ME ACHP-H16/4R3HA-M (NE) ACHP-H16/5R3HA-M					
Air-to-water heat ump:		yes					
Water-to-water heat pump:		no					
Brine-to-water heat pump:		no					
Low-temperature heat pump:		no					
Equipped with a supplementary heater:		no					
Heat pump combination heater:		no					
Declared climate condition		Colder					
Declared temperature application		Medium					
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output(*)	Prated	11.8	kW	Seasonal space heating energy efficiency	ηs	121	%
Declared capacity for heating for part load at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	7.64	kW	Tj = -7°C	COPd	2.65	-
Tj = +2°C	Pdh	4.42	kW	Tj = +2°C	COPd	3.79	-
Tj = +7°C	Pdh	2.97	kW	Tj = +7°C	COPd	4.81	-
Tj = +12°C	Pdh	3.43	kW	Tj = +12°C	COPd	6.29	-
Tj = bivalent temperature	Pdh	9.61	kW	Tj = bivalent temperature	COPd	1.86	-
Tj = operation limit temperature	Pdh	5.21	kW	Tj = operation limit temperature	COPd	1.23	-
For air-to-water heat pumps: Tj = -15°C (ifTOL<-20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C (ifTOL<-20°C)	COPd	-	-
Bivalent temperature	Tbiv	-15	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-22	°C
Cycling interval capacity for heating	Pcyc	-	kW	Cycling interval efficiency	COPcyc	-	-
Degradation co-efficient(**)	Cdh	0.9	-	Heating water operating limit temperature	WTOL	52	°C
Power consumption in modes other than active mode				Supplemantary heater			
Off mode	P OFF	0.020	kW	Rated heat output (*)	Psup	6.59	kW
Thermostat-off mode	ᵖTO	0.030	kW	Type of energy input	Electricity		
Standby mode	P SB	0.020	kW				
Crankcase heater mode	ᵖCK	0.000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	4000	m³/h
Sound power level.	LWA	-	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m³/h
Annual energy consumption	QHE	9362	kWh				
For heat pump combination heater							
Declaед load profile	-			Water heating energy efficiency	Owh	-	%
Daily electricity consumption	Qelec	-	kWh	Daily fuel consumption	Qfuel	-	kWh
Contact details	AUX Co., Ltd 1166 Mingguang North Road, Jiangshan Yinzhou District, Ningbo, 315191 Zhejiang, China						
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9							